



Declaration of Product Performance No. 11/2018

Identification code of the product **BEATRIX - BC 601 R, BC 602 R**

Type Prefabricated concrete paving with two layers acc. to CSN EN 1339

Intended use Concrete paving is suitable for flooring indoor and outdoor surfaces. They are not suitable for use in chemically aggressive environments.

Manufacturer CIDEMAT Hranice, spol. s r.o., Skalní 1088, 753 01 Hranice
plant Belotínská cesta 288, 753 01 Hranice, Czech Republic
Id-No.: 49606786

System of performance assessment and verification 4

Notified body TZUS Prague, Prosecká 811/76a, 190 00 Prague 9

Basic characteristic	Property	Harmonized technical specification
Reaction to fire	A1 fl	CSN EN 1339
Weather resistance (kg/m ²)	NPD (for indoor use)	
	0,055 (for outdoor use)	
Water absorption (%hm)	max. 6	
Bending strength (Mpa)	min. 6	
Skid / slip resistance	satisfactory	
Thermal conductivity (W/(m·K))	NPD	
Breaking load (cm ³)	max. 26	

The properties of the products are in conformity with characteristics listed in the table. Determined on the basis of the Concrete Paving Test Protocol No. 070-053345 dated 5.9.2017

Hranice 22.5.2018


Radek Hlavinka
Company Manager

CIDEMAT Hranice, s.r.o.
Skalní č. 1088
Hranice I - Město
753 01 HRANICE